

Lifting mast (see-through model)

- With category 2 three-point linkage as standard
- Mast width 770 mm
- Fork carriage width 1200 mm (FEM2)
- Fork length 1190 mm (foldaway)
- Adjustable fork width
- Lifting capacity calculated at 180 bar
- Drive-through height calculated with lower hitch point height 300 mm above the ground
- With wagon drawbar
- Complete with hydraulic hoses and quick connectors

Tractor specifications desired for solid construction of the lifting mast on the front of the tractor.
This type of lifting mast is not suitable in combination with a forward tipping box rotator.

Type	Lift height	Lifting capacity	Headroom	Weight	Price
HMD 200/2000	2000 mm	2000 kg	1800 mm	595 kg	€ 6350,-
HMD 240/2000	2400 mm	2000 kg	2000 mm	615 kg	€ 6450,-
HMD 280/2000	2800 mm	2000 kg	2200 mm	635 kg	€ 6550,-
HMD 240/2500	2400 mm	2500 kg	2000 mm	625 kg	€ 6775,-
HMD 280/2500	2800 mm	2500 kg	2200 mm	645 kg	€ 6875,-
HMD 340/2500	3400 mm	2500 kg	2500 mm	680 kg	€ 7050,-
HMD 400/2500	4000 mm	2500 kg	2800 mm	710 kg	€ 7225,-

Options

- Solid construction of liftingmast on front of the tractor instead of three-point € 200,-
- Accessories lifting masts

