

## Rubber scraper

- Rubber scraper for use on farmyard, roads, stables, etc.
- With rubber (35 mm thick)
- Rubber is reversible
- Standard model can be used both on tractor three-point linkage (cat. 2) and forklift
- When using a Euro or Accord connection, the tractor three-point linkage (cat. 2) and forklift connection can't be used anymore
- Type MS-275-DV(H) is adjustable to the left or right side, up to a max. of 45° (7 positions)
- Fork Sleeves: MS275-S(Z)/MS275-DV(H): 150x50-L340 mm, c.t.c. 800 mm

Type	Description	Working width	Weight	Price
MS275-S	3-punt	2.650 mm	145 kg	€ 900,-
MS275-SV	Euro	2.650 mm	145 kg	€ 1150,-
MS275-DV	3-punt	2.650 mm	235 kg	€ 2075,-
MS275-DVV	Euro	2.650 mm	235 kg	€ 2325,-
MS275-DVH	3-punt	2.650 mm	260 kg	€ 2675,-
MS275-DVHV	Euro	2.650 mm	260 kg	€ 2925,-

S - fixed model

SZ - fixed model, galvanized

DV - rotatable

DVH - hydr. rotatable

### Options

- Rubber reinforced with canvas (2750x400x35 mm), including bolts € 375,-



MS275-S

