

Box rotator with integrated side-shift

- Maximum box width: 1800 mm
- 180° rotation angle (left rotation as standard)
- Open construction for optimal visibility on the forklift forks
- Folding third fork using gas spring
- Third fork in width adjustable
- High quality tipping shaft with sleeve bearing
- Integrated side-shift (200 mm)
- Including hoses and quick connectors
- Four-hose connections as standard
- Excluding forklift forks

Type	Maximum load	Height of the fork carrier	Frontal extension length	Center of gravity	Height third fork*	Fork carrier width	Weight	Price
SK54A	2500 kg	FEM2: 407 mm	173 mm	141 mm	660 mm	1000 mm	335 kg	€ 4375,-
SK54C	3500 kg	FEM3: 508 mm	188 mm	145 mm	760 mm	1200 mm	405 kg	€ 4875,-

* Calculated from the top of the fork to the bottom of the fork carrier

Options

- Electrical hydraulic switching valve € 300,-
- Rotation angle up to 200° I/O 180° € 175,-
- Right rotated instead of left rotated € 200,-
- Topfork (detachable) € 400,-
- Hydraulic connection (not turning) € 200,-
- Rapid coupling € 275,-
- Adjustable ball bearing instead of sleeve bearing € 825,-
- Attachment to frontloader or reachtruck



Kistenkantelaar met sideshift SK54C



Kistenkantelaar met sideshift SK54C