

Stationary box rotator

- Stationary box rotator with a maximal tipping angle of 142°
- Standard discharge height 1100 mm
- Hydraulic unit and control directly at frame (both left and right possible)
- Adjustable for box heights between 800 - 1400 mm
- Maximal box depth 1200 mm
- Adjustable discharge hopper
- Easily moved with forklift truck
- Equipped with a CEE contra plug (5 pin)

Type	Max. capacity	Total width	Weight	Price
K60-1200	2000 kg	1720 mm	855 kg	€ 8550,-
K60-1400	2000 kg	1920 mm	875 kg	€ 8775,-
K60-1600	2000 kg	2120 mm	895 kg	€ 9000,-
K60-1800	2000 kg	2320 mm	915 kg	€ 9225,-
K60-2000	2000 kg	2520 mm	935 kg	€ 9450,-
K60-2240	2000 kg	2760 mm	1015 kg	€ 9675,-
K60-2400*	2000 kg	2920 mm	1060 kg	€ 9900,-

* Fixed discharge funnel instead of adjustable discharge funnel

Options

Wireless remote control

- Wireless remote control, 2-button, direct control (including control on frame by switch)
- Range: approx. 100 meters (depending on the environment)

Automatic tilt control

Tipper automatically tilts forward. Once fully tilted, the box rotator shocks several times.

- Walk-in protection with 2 photocells
- Wired pendant push button station for both automatic and manual operation

Options



Stationaire kistenkantelaar



K60 kistenkantelaar