Box rotator

- Maximum box width: 1800 mm
- 180° rotation angle (left rotation as standard)
- Open construction for optimal visibility on the forklift forks
- Plug-in or folding third fork with gas spring
- Third fork in width adjustable
- High quality tipping shaft with sleeve bearing
- Including hoses and quick connectors
- Excluding forklift forks

Equipped with durable and replaceable sprocket and gear rack (width 50 mm)

Find dealer

Type	Maximum load	Heigth of the fork carrier	Frontal extension length	Center of gravity	Heigth third fork*	Fork carrier width	Weight	Price
K54A-I *	2500 kg	FEM2: 407 mm	165 mm	133 mm	360 mm	1000 mm	240 kg	€ 3350,-
K54A-O *	2500 kg	FEM2: 407 mm	165 mm	158 mm	660 mm	1000 mm	270 kg	€ 3700,-
K54C-I *	3500 kg	FEM3: 508 mm	185 mm	134 mm	460 mm	1200 mm	315 kg	€ 3975,-
K54C-O *	3500 kg	FEM3: 508 mm	185 mm	158 mm	760 mm	1200 mm	345 kg	€ 4325,-

* I = plugin model, O = foldaway model
* Calculated from the top of the fork to the bottom of the fork carrier

Options

- Rotation angle up to 200° I/O 180° € 200,-
- Right rotated instead of left rotated € 250,-
- Topfork (detachable) € 450,-
- Hydraulic connection on fork carrier (rotating, not possible in combination with 200° rotation angle) € 325,-
- Hydraulic connection (not rotating) € 225,-
- Rapid coupling € 325,-
- Adjustable ball bearing instead of sleeve bearing € 950,-
- Attachment to frontloader or reachtruck



Kistenkantelaar K54C-O



Kistenkantelaar K54C-I